

■ Alloy steel chain (grade 100)

Type	Diameterd	Pitchp	Inside Width (Min.)	Outside Width (Max.)	W.L.L.		P.L.	B.L.	Weight Kg/m
					JIS Standard	ISO			
V-5	5	15	6.3	17.5	0.80	1.0	2.0	4.0	0.544
* V-6	6	18	7.5	21.0	1.1	1.4	2.8	5.6	0.782
V-6.3	6.3	19	7.9	22.0	1.25	1.4	3.15	6.3	0.860
V-7.1	7.1	21	8.9	25.0	1.6	2.0	4.0	8.0	1.10
V-8	8	24	10.0	28.0	2.0	2.5	5.0	10	1.39
V-9	9	27	11.3	31.5	2.5	3.1	6.3	12.5	1.76
V-10	10	30	12.5	35.0	3.15	4.0	8.0	16	2.17
V-11.2	11.2	34	14.0	39.0	4.0	5.0	10	20	2.71
* V-13	13	39	16.3	46.0	5.0	6.2	12.5	25	3.67
V-16	16	48	20.0	56.0	8.0	10	20	40	5.56

■ Alloy steel chain (grade 80)

Type	Diameterd	Pitchp	Inside Width (Min.)	Outside Width (Max.)	W.L.L.		P.L.	B.L.	Weight Kg/m
					JIS Standard	ISO			
T-5	5	15	6.3	17.5	0.63	0.80	1.6	3.2	0.544
* T-6	6	18	7.5	21.0	0.90	1.1	2.3	4.5	0.782
T-6.3	6.3	19	7.9	22.0	1.0	1.2	2.6	5.1	0.860
T-7.1	7.1	21	8.9	25.0	1.3	1.6	3.3	6.5	1.10
T-8	8	24	10.0	28.0	1.6	2.0	4.2	8.2	1.36
T-9	9	27	12.5	32	2.0	2.5	5.1	10.2	1.76
T-10	10	30	12.5	35.0	2.6	3.2	6.5	13	2.17
* T-11.2	11.2	34	14.0	39.0	3.2	4.0	8.0	16	2.71
T-13	13.2	39	16.3	46.0	4.4	5.5	11	22	3.67
T-16	16	48	20.0	56.0	6.6	8.0	17	33	5.56
* T-20	20	60	25.0	70.0	10	13	26	52	8.69
T-22	22	66	28.0	77.0	12.5	15	31.5	63	10.5
T-25	25	75	32.0	88.0	16	20	40	80	13.6
T-28	28	84	35.0	98.0	20	25	50	100	17.0
T-32	32	96	40.0	112	24	30	60	120	22.2

