



Beam Clamps TBC Type

Model	TBC-1	TBC-2	TBC-3	TBC-5	TBC-10
Capacity (tonnes)	1	2	3	5	10
Proof Load (kN)	14.71	29.42	44.13	61.29	125
I-Beam Width (mm)	75-220	75-220	80-320	80-320	80-350
Dimensions (mm)	Max. A	260	260	354	400
	Min. B	180	180	235	235
	Max. B	360	360	490	490
	C	64	74	103	110
	D	5	6	8	10
	E	215	215	260	260
	Max. F	155	155	225	225
	Min. F	102	102	140	140
Net Weight (kg)	H	22	22	24	28
		4.5	5	10.5	11



Wire Rope Grip WRG Type

Model	WRG-10	WRG-14	WRG-20	WRG-26	WRG-28
Capacity (tonnes)	1	2	3	5	6
Wire Rope Dia. (mm)	8~10	12~14	16~20	22~26	28~32
Dimensions (mm)	A	11	16	20	28
	B	33	40	45	48
	C	16	24	32	36
	H	36	45	61	67
	W	71	90	134	140
Net Weight (kg)	1.5	2.25	5.07	7.24	7.77



Snatch Block

Model	Size	Capacity (tonnes)	H (mm)	W (mm)	Hook L (mm)	Eye L (mm)	Rope Dia. (mm)	Net Wt. (kg)
50X1S	2"	0.25	35	57	210	185	6	0.3
75X1S	3"	0.5	36	87	265	263	8	1.7
100X1S	4"	1	48	112	330	310	10	3.2
125X1S	5"	1.5	56	140	400	376	13	5
150X1S	6"	2	64	168	458	402	16	8.3
50X2S	2"	2.5	60	57	210	185	6	0.5
75X2S	3"	0.5	65	87	265	263	8	3
100X2S	4"	1	93	112	322	304	10	4.7
125X2S	5"	1.5	94	140	400	376	13	8
150X2S	6"	2	106	168	458	402	16	13.5